

AD 490

Doosan
Mecc Alte
D+ &



ISO8528 GC,) &

SZUTEST GC - \$\$\$

CE

2000/14/EC &\$\$#(#

z) \$ z'z' D:

	"	"	"	"	Amp
400/230	485,00	388,00	425,00	340,00	613,00

Standard Specifications

z

fl ! E

z

z

ALTERNATOR

D; A Ž 5JF

fl

fl " E

fl \$\$\$ \$\$\$

fl " \$ E

TRANSFER SWITCH

fl

AD 490

Doosan
Mecc Alte
D+' &'

Manufacturer		Doosan		
Model		P158LE		
		%\$\$' "# "		
		(%(' " Q)) < DQ		
	L	14,60		
	"	128 x 142		
		15,0:1		
	fl # ı	"# "	1500	
	fl ı	L	28,00	
		L	88,00	
AbsorbedAirDischargeReSourceKey.Text	' # "	25,50		
	' # "	410		
	' # "	78,30		
	° C	580		
		24 V d.c.		
	Load	%\$\$ı	'+)ı)\$ı
	# "	89,30	65,00	44,00

		Mecc Alte		
		ECO 40-2S/4		
	Hz	50		
	"	450		
7cg'		0,80		
		3		
	fl ı	400/230		
	A	649		
Temperatur		H		

		fl ı		fl ı	
	"	"	"	"	L
AD 490	3210	3360	1400	2040	800
		fl ı		fl ı	
	"	"	"	"	L
AK 81	4660	4900	1600	2500	850

AD 490

Doosan
Mecc Alte
D+&''



f@#@Bt
f@#@Bt
"
"
"
"
"
"
f@#@Bt

971

#

#

#

#



#

6G`9B`*\$-)\$

6G`9B`*\$\$\$!*!&

6G`9B`*\$\$\$!*!(

f&)(, t
f&)% +t
f&)% \$t

GA 8

") z z
% , !&* \$ " &(\$) z z
z " " "

AD 490

Doosan
Mecc Alte
D+ &''

5? , %!



- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10

f! \$\$\$! '%&\$\$' Ł

'&\$\$\$#/(# "

	"	1600
f! "Ł	"	4900
f! "Ł	"	2500
		850